



COB 500 Series

Specification Sheet



Performance Table

SKU	Length	CCT	Lumens
LC-COB-500-30-16	16.4ft	3000K	Up to 530lm/ft
LC-COB-500-40-16	16.4ft	4000K	Up to 530lm/ft
LC-COB-500-50-16	16.4ft	5000K	Up to 530lm/ft

Specifications

Input Voltage:	24VDC
CRI:	90+
Power:	4.6W/ft
Lumens:	530lm/ft
Cut Length:	1.97" (50 mm)
Environment:	IP20
Dimensions (W x H):	0.39" x 0.05"
Beam Angle:	180°
Maximum Run:	32.8ft (98.4 Watts)
Lamp Life:	50,000 Hours
Operating Temp:	-4°F to 113°F (-20°C to 45°C)
Adhesive:	3M
Warranty:	6 years
Dimming Control:	Incandescent • CFL/LED • MLV ELV • 0-10V • Dimmer switch / wireless app & wall switch

Connectors and Wires

ENO-SC-TT-10	0.39" (10mm) Tape to Tape screw connectors
ENO-SC-TW-10	0.39" (10mm) Tape to Wire screw connectors
ENO-SC-LL-10	0.39" (10mm) L Shape 90° screw connectors
ENO-SC-TW-72W-10	0.39" (10mm) Tape to wire screw connectors with a 72" lead wire
WS-2P-15	15ft 2 Pin 15ft Wire Spool
WS-2P-250	250ft 2 Pin 250ft Wire Spool

Mechanical Diagrams

