

MaxCut

Specification Sheet



Specifications

Input Voltage:	24VDC
CRI:	90+
Power:	3.3W/ft
Lumens:	251lm/ft - 286lm/ft
Cut Length:	Any Length
Environment:	IP20
Dimensions (W x H):	0.31" x 0.06"
Beam Angle:	145°
Maximum Run:	32.8ft (98.4 Watts)
Lamp Life:	50,000 Hours
Operating Temp:	-4°F to 113°F (-20°C to 45°C)
Adhesive:	3M
Warranty:	6 years
Dimming Control:	Incandescent • CFL/LED • MLV ELV • 0-10V

Connectors and Wires

ENO-SC-TT-8	0.31" (8mm) Tape to tape screw connectors
ENO-SC-TW-8	0.31" (8mm) Tape to wire screw connectors
ENO-SC-LL-8	0.31" (8mm) L Shape 90° screw connectors
ENO-SC-TW-72W-8	0.31" (8mm) Tape to wire screw connectors with a 72" lead wire
WS-2P-15	15ft 2 Pin 15ft Wire Spool
WS-2P-250	250ft 2 Pin 250ft Wire Spool

Performance Table

SKU	Length	CCT	Lumens
MaxCut-27-16	16.4ft	2700K	251lm/ft
MaxCut-30-16	16.4ft	3000K	262lm/ft
MaxCut-35-16	16.4ft	3500K	262lm/ft
MaxCut-40-16	16.4ft	4000K	286lm/ft
MaxCut-50-16	16.4ft	5000K	280lm/ft
MaxCut-27-100	100ft	2700K	251lm/ft
MaxCut-30-100	100ft	3000K	262lm/ft
MaxCut-35-100	100ft	3500K	262lm/ft
MaxCut-40-100	100ft	4000K	286lm/ft
MaxCut-50-100	100ft	5000K	280lm/ft

Mechanical Diagrams

