

UniColor IP20

Specification Sheet



Specifications

Input Voltage:	24VDC
CRI:	90+
Power:	2.2W/ft.
Lumens:	Up to 220Lm/ft
Cut Length:	1.64" (41.67mm)
Environment:	IP20
Dimensions (W x H x L):	0.47" x 0.06" x 197"
Beam Angle:	150°
Maximum Run:	32.8ft (74Watts)
Lamp Life:	50,000 Hours
Max Ambient Temperature:	113°F
Adhesive:	3M
Warranty:	6 years
Color Temperature:	RGB + CCT (2700-6000K)

Connectors and Wires

Uni-6P-TW-72W-12	Tape-to-wire snap connector with 72" wire
Uni-6P-TW-12	Tape-to-wire snap connector
Uni-6P-TT-12	Tape-to-tape snap connector
Uni-6P-TT-6W-12	Tape-to-tape snap connector with 6" wire
WS-6P-32	32ft, 6 Pin RGB+CCT Wire Spool

Performance Table

SKU	Length	CCT	Lumens
Uni-RGBCW-16	16.4ft	RGB + CCT (2700-6000K)	Up to 220lm/ft
Uni-RGBCW-100	100ft	RGB + CCT (2700-6000K)	Up to 220lm/ft
Uni-RGBCW-LC	Left Corner 90° Tape	RGB + CCT (2700-6000K)	Up to 220lm/ft
Uni-RGBCW-RC	Right Corner 90° Tape	RGB + CCT (2700-6000K)	Up to 220lm/ft

Mechanical Diagrams

